

GASKET MATERIAL GUIDE

| Temperature | -6 |
|------------------|----|
| Acid | |
| Akaii | F |
| Fats/Oils | (|
| Taste | |
| Odor | |
| Abrasion Resist | |
| Compression Test | |

| Buna-N | |
|--------------|--|
| 65° to 210°F | |
| Good | |
| Fair to Good | |
| Good to Ex. | |
| Good | |
| Good | |
| Excellent | |
| Good | |

| EPDM | FLURO- ELASTOMER |
|--------------|---------------------|
| 60° to 300°F | -20° to 350°F |
| Good to Ex. | Good to Ex. |
| Good to Ex. | Poor to Good |
| Poor | Good to Ex. |
| Good | Good |
| Good | Good |
| Good | Good |
| Fair | Good to Ex. |

| Temperature |
|-------------------------|
| Acid |
| Akaii |
| Fats/Oils |
| Taste |
| Odor |
| Abrasion Resist |
| Compression Test |

| PTFE |
|---------------|
| -40° to 450°F |
| Good to Ex. |
| Excellent |
| Excellent |
| Excellent |
| Excellent |
| Fair |
| Cold Flows |
| |

-80° to 450°F Poor to Good Poor to Fair Poor to Good Good Good Poor Good to Ex.

Polyethylene -20° to 150°F Good Good Good Excellent Excellent Fair Cold Flows