



Premium Manufacturer of Sanitary Fittings, Valves, Pumps, & More

# CLEAR ACRYLIC SIGHT TUBES

Steel & O'Brien is pleased to announce our new line of clear acrylic sight tubes. These see-through spool sections are ideal for simple and quick sight requirements. Made from ASTM 5436-D, FDA-conforming acrylic, our tubes can be clamped into your sanitary line seamlessly.

## FEATURES AND SPECIFICATIONS

- Clear acrylic sight tubes are ideal for simple sight requirements as well as tank level indication
- These acrylic tubes comply with the code of federal regulations CFR177.1010
- An economical option to standard stainless steel sight glasses
- Standard clamp torque is required (25 in/lbs)
- The minimum length is 1.25" OAL
- Other sizes priced on the application
- Pressure ratings absent thermal shock

*Not recommended for use with abrasive products. Do not use 2-bolt high-pressure clamps.*



Part Number	Clamp Size	Length	Maximum Cold Working Pressure (PSI) (@70°F)	Pressure (PSI) @ Maximum Allowable Temp. (@140°F)	Inside Diameter (Reference ID)	Outside Diameter (Reference OD)
54SPOOLMP-1.5X5.875	1.5"	5.875"	145	100	1.295"	2"
54SPOOLMP-2X5.875	2"	5.875"	145	100	1.835"	2.625"
54SPOOLMP-3X7.500	3"	7.500"	120	75	2.817"	3.625"
54SPOOLMP-4X7.625	4"	7.625"	75	30	3.750"	4.750"

*Standard lengths shown, other lengths available upon request. Maximum lengths for 1-1/2" & 2" sizes = 48"  
Maximum lengths for 3" & 4" sizes = 7.625"*

Simplifying Sanitary Through Superior Service™

7869 Route 98, Arcade, New York 14009  
Tel: (585) 492-5800  
sales@sob.us

© Steel & O'Brien Mfg. Inc.  
Form No.004 10/22

